

# Panel Light



## FZL-PL30-01-28 Series (300 x 300 mm)


28W

### Specifications

- Luminous Flux (lm): 1400 (±10%) with 3000K / 1550 (±10%) with 4000K / 1800 (±10%) with 6000K
- Power Consumption (W): 28
- LED: **Liteon**
- CCT (K): 3000K (WW) / 4000K (NW) / 6000K (CW)
- Lifetime (hrs): >35000
- Beam Angle: 120°
- Net Weight (kgs): 2.2 (±10%) with driver

Model	FZL-PL30-01-WW-28 FZL-PL30-01-NW-28 FZL-PL30-01-CW-28	FZL-PL30-01-WW-28TDH FZL-PL30-01-NW-28TDH FZL-PL30-01-CW-28TDH	FZL-PL30-01-WW-28TDL FZL-PL30-01-NW-28TDL FZL-PL30-01-CW-28TDL
Input Voltage (V)	AC 100 – 240V (Non-dimmable)	AC 220 – 240V (TriAC dimmable)	AC 100 – 120V (TriAC dimmable)

### Dimension



## FZL-PL60-01-42 Series (600 x 600 mm)

42W

### Specifications

- Luminous Flux (lm): 2400 (±10%) with 3000K / 2500 (±10%) with 4000K / 3400 (±10%) with 6000K
- Power Consumption (W): 42
- LED: **Liteon**
- CCT (K): 3000K (WW) / 4000K (NW) / 6000K (CW)
- Lifetime (hrs): >35000
- Beam Angle: 120°
- Net Weight (kgs): 4.5 (±10%) with driver

Model	FZL-PL60-01-WW-42 FZL-PL60-01-NW-42 FZL-PL60-01-CW-42	FZL-PL60-01-WW-42TDH FZL-PL60-01-NW-42TDH FZL-PL60-01-CW-42TDH	FZL-PL60-01-WW-42TDL FZL-PL60-01-NW-42TDL FZL-PL60-01-CW-42TDL
Input Voltage (V)	AC 100 – 240V (Non-dimmable)	AC 220 – 240V (TriAC dimmable)	AC 100 – 120V (TriAC dimmable)

## FZL-PL60-01-52 Series (600 x 600 mm)

52W

### Specifications

- Luminous Flux (lm): 2900 (±10%) with 3000K / 3050 (±10%) with 4000K / 4200 (±10%) with 6000K
- Power Consumption (W): 52
- LED: **Liteon**
- CCT (K): 3000K (WW) / 4000K (NW) / 6000K (CW)
- Lifetime (hrs): >35000
- Beam Angle: 120°
- Net Weight (kgs): 4.5 (±10%) with driver

Model	FZL-PL60-01-WW-52 FZL-PL60-01-NW-52 FZL-PL60-01-CW-52	FZL-PL60-01-WW-52TDH FZL-PL60-01-NW-52TDH FZL-PL60-01-CW-52TDH	FZL-PL60-01-WW-52TDL FZL-PL60-01-NW-52TDL FZL-PL60-01-CW-52TDL
Input Voltage (V)	AC 100 – 240V (Non-dimmable)	AC 220 – 240V (TriAC dimmable)	AC 100 – 120V (TriAC dimmable)

### Dimension

